


1. Identification

Product identifier	Nukote Chemshield TS - Side A
Other means of identification	None.
Recommended use	Concrete Surface Protection. For further information, Refer to the Product Technical Data Sheet.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Supplier	
Company name	Nukote Coating Systems International
Address	2051 Reliance Parkway Bedford TX. 76021
Telephone	832-770-7100
Email	SDS@nukoteglobal.com
Emergency Phone Number	Chemtrec: 800-424-9300 (Account: CCN1217) or International: 703-527-3887 (Account: CCN1217)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1A
	Specific target organ toxicity, repeated exposure	Category 1 (lung)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		

Signal word	Danger
Hazard statement	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause cancer. Causes damage to organs (lung) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.
Storage	Store locked up.

Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	48.64% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 48.64% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Epoxy Resin	25068-38-6	35 - 60
Aluminum oxide	1344-28-1	20 - 35
Silicon Dioxide	67762-90-7	10 - 25
Epoxy Resin	28064-14-4	0 - 25
Magnesium Silicate	14807-96-6	5 - 20
Titanium dioxide	13463-67-7	1 - 10
Crystalline Silica	14808-60-7	1 - 5
Fumed Silica	112945-52-5	0 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Provide eyewash station. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Causes skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects. May cause cancer.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Fumed Silica (CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	
Magnesium Silicate (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Crystalline Silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Crystalline Silica (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
Fumed Silica (CAS 112945-52-5)	TWA	6 mg/m ³	
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other

Wear appropriate chemical resistant clothing. Wash hands thoroughly after handling. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid

Form

Liquid

Color

Light Grey.

Odor

Low.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

Not available.

Flash point

Not available.

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	13.5 lb/gal (77 °F (25 °C))
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Paste
Viscosity temperature	77 °F (25 °C)
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Avoid extremely high temperatures. Freezing temperatures. Moisture.
Incompatible materials	Acids. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Causes skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects. May cause cancer.

Information on toxicological effects

Acute toxicity May cause an allergic skin reaction.

Components	Species	Test Results
Epoxy Resin (CAS 25068-38-6)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Magnesium Silicate (CAS 14807-96-6)		
Acute		
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Titanium dioxide (CAS 13463-67-7)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 2.28 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	> 11000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	May cause cancer. Crystalline silica has been classified by IARC, NTP and ACGIH as a known human carcinogen and suspected human carcinogen respectively.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Crystalline Silica (CAS 14808-60-7)	1 Carcinogenic to humans.	
Fumed Silica (CAS 112945-52-5)	3 Not classifiable as to carcinogenicity to humans.	
Magnesium Silicate (CAS 14807-96-6)	2B Possibly carcinogenic to humans.	
Titanium dioxide (CAS 13463-67-7)	3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans.	
NTP Report on Carcinogens		
Crystalline Silica (CAS 14808-60-7)	Known To Be Human Carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Causes damage to organs (lung) through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Epoxy Resin (CAS 25068-38-6)		
Fish	LC50	Salmo gairdneri
		1.5 mg/l, 96 hours
Aquatic		
Crustacea	EC50	Daphnia magna
		2.7 mg/l, 48 hours
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum oxide	1344-28-1	20 - 35

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Aluminum oxide (CAS 1344-28-1)
Crystalline Silica (CAS 14808-60-7)
Fumed Silica (CAS 112945-52-5)
Magnesium Silicate (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum oxide (CAS 1344-28-1)

Crystalline Silica (CAS 14808-60-7)
Magnesium Silicate (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum oxide (CAS 1344-28-1)
Crystalline Silica (CAS 14808-60-7)
Fumed Silica (CAS 112945-52-5)
Magnesium Silicate (CAS 14807-96-6)
Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Aluminum oxide (CAS 1344-28-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline Silica (CAS 14808-60-7)
Epoxy Resin (CAS 25068-38-6)
Titanium dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	20-MAY-2021
Revision date	-
Version #	01
Further information	HMIS Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe
HMIS® ratings	Health: 3* Flammability: 0 Physical hazard: 0

NFPA ratings



Disclaimer

NuKote Coating Systems cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

1. Identification

Product identifier Nukote Chemshield TS - Side B
Other means of identification None.
Recommended use Surface Protection. For Further Information, Refer to the Product Technical Data Sheet.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company name Nukote Coating Systems International
Address 4730 Consulate Plaza Dr.
 Suite 100
 Houston, TX. 77032
Telephone 832-770-7100
Email SDS@nukoteglobal.com
Emergency Phone Number Chemtrec: 800-424-9300 (Account: CCN16118) or International: 703-527-3887 (Account: CCN16118)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards

Acute toxicity, oral	Category 4
Acute toxicity, dermal	Category 4
Acute toxicity, inhalation	Category 4
Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1
Sensitization, skin	Category 1
Reproductive toxicity	Category 2

Environmental hazards

Hazardous to the aquatic environment, acute hazard	Category 3
Hazardous to the aquatic environment, long-term hazard	Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Isophorone diamine	2855-13-2	19 - 45
Diethylenetriamine	111-40-0	10 - 30
m-Phenylenebis(methylamine)	1477-55-0	9 - 15
4,4'-isopropylidenediphenol	80-05-7	6 - 16
Benzyl alcohol	100-51-6	5 - 10

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Harmful if swallowed. Nausea, vomiting. Harmful in contact with skin. Harmful if inhaled. Coughing. Difficulty in breathing. Causes severe skin and eye burns. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause an allergic skin reaction. Rash. Dermatitis. Suspected of damaging fertility or the unborn child.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use water spray to reduce vapors or divert vapor cloud drift. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store in a well-ventilated place.

8. Exposure controls/personal protection : Exposure Time : 45 minutes

Occupational exposure limits Observation Time : 14 days

US. ACGIH Threshold Limit Values

Components	Type	Value
Diethylenetriamine (CAS 111-40-0)	TWA	1 ppm
m-Phenylenebis(methylamine) (CAS 1477-55-0)	Ceiling	0.1 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Diethylenetriamine (CAS 111-40-0)	TWA	4 mg/m3
m-Phenylenebis(methylamine) (CAS 1477-55-0)	Ceiling	1 ppm 0.1 mg/m3

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Benzyl alcohol (CAS 100-51-6)	TWA	44.2 mg/m3 10 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Diethylenetriamine (CAS 111-40-0) Can be absorbed through the skin.
m-Phenylenebis(methylamine) (CAS 1477-55-0) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Diethylenetriamine (CAS 111-40-0) Skin designation applies.

US - Tennessee OELs: Skin designation

m-Phenylenebis(methylamine) (CAS 1477-55-0)	Can be absorbed through the skin.
---	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

Diethylenetriamine (CAS 111-40-0)	Can be absorbed through the skin.
m-Phenylenebis(methylamine) (CAS 1477-55-0)	Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Diethylenetriamine (CAS 111-40-0)	Can be absorbed through the skin.
m-Phenylenebis(methylamine) (CAS 1477-55-0)	Can be absorbed through the skin.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Physical state	Liquid
Form	Liquid
Color	Straw to Yellow.

Odor Strong ammonia.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 9.01 lb/gal (77 °F (25 °C))

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	paste
Viscosity temperature	77 °F (25 °C)
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids. Alkaline metals. Peroxides. Phenols.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Harmful if swallowed. Nausea, vomiting. Harmful in contact with skin. Harmful if inhaled. Coughing. Causes severe skin burns and eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause allergic skin reaction. Rash. Dermatitis. Suspected of damaging fertility or the unborn child.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. May cause an allergic skin reaction.

Components	Species	Test Results
4,4'-isopropylidenediphenol (CAS 80-05-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	3000 mg/kg
<i>Oral</i>		
LD50	Rat	3300 - 4100 mg/kg
Benzyl alcohol (CAS 100-51-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	8.8 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	1230 - 3100 mg/kg
Diethylenetriamine (CAS 111-40-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	550 mg/kg

Components	Species	Test Results
<i>Oral</i> LD50	Rat	1080 mg/kg
m-Phenylenebis(methylamine) (CAS 1477-55-0)		
Acute		
<i>Dermal</i> LD50	Rabbit	2000 mg/kg
<i>Inhalation</i> LC50	Rat	3.75 mg/l, 1 Hours
<i>Oral</i> LD50	Rat	930 mg/kg
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
NTP Report on Carcinogens		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results	
4,4'-isopropylidenediphenol (CAS 80-05-7)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	10.2 mg/l, 48 Hours
Fish	LC50	Pimephales promelas	4.6 mg/l, 96 Hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	> 3.146 mg/l, 21 days

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

4,4'-isopropylidenediphenol (CAS 80-05-7)	3.32
Benzyl alcohol (CAS 100-51-6)	1.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. (Nukote Chemshield -TS (Part B))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B2, IB2, T11, TP1, TP27
Packaging exceptions	154
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. ((Nukote Chemshield -TS (Part B))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	II
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. ((Nukote Chemshield -TS (Part B))
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

4,4'-isopropylidenediphenol (CAS 80-05-7) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - No
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
4,4'-isopropylidenediphenol	80-05-7	6 - 16

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. Massachusetts RTK - Substance List**

4,4'-isopropylidenediphenol (CAS 80-05-7)
 Benzyl alcohol (CAS 100-51-6)
 Diethylenetriamine (CAS 111-40-0)
 m-Phenylenebis(methylamine) (CAS 1477-55-0)

US. New Jersey Worker and Community Right-to-Know Act

4,4'-isopropylidenediphenol (CAS 80-05-7)
 Diethylenetriamine (CAS 111-40-0)
 Isophorone diamine (CAS 2855-13-2)
 m-Phenylenebis(methylamine) (CAS 1477-55-0)

US. Pennsylvania Worker and Community Right-to-Know Law

4,4'-isopropylidenediphenol (CAS 80-05-7)
 Benzyl alcohol (CAS 100-51-6)
 Diethylenetriamine (CAS 111-40-0)
 m-Phenylenebis(methylamine) (CAS 1477-55-0)

US. Rhode Island RTK

4,4'-isopropylidenediphenol (CAS 80-05-7)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

4,4'-isopropylidenediphenol (CAS 80-05-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	20-MAY-2021
Revision date	-
Version #	01
Further information	HMIS Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe
HMIS® ratings	Health: 3* Flammability: 0 Physical hazard: 0

NFPA ratings



Disclaimer

NuKote Coating Systems cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.